

**FRONT**

**EarthWorks™**

Growth products for professional turf management

**Base One**

1-10-10 with traces

**Liquid Fertilizer**

Liquid fertilizer

Macro and micro nutrients

Low nitrogen/iron formulation

23Lbs (10.4Kg)  
(2.5 gallons / 9.5 liters)

## **BACK**

# **Base One**

**1-10-10 with traces**

**Liquid Fertilizer**

### **Use Instructions**

#### **Bi-Weekly Maintenance**

Apply 2 to 4 ounces per 1000 sq. ft. every 2 weeks in 2 gallons of water. Tank mix nitrogen, calcium, iron and other fertility as needed.

Increase application rate based on the need for phosphorus or potassium

*Always do a compatibility test before spraying any mix.*

### **Guaranteed Analysis**

Total Nitrogen (N)	1.00%
0.30% Ammoniacal Nitrogen	
0.35% Nitrate Nitrogen	
0.35% Urea Nitrogen	
Available Phosphate (P <sub>2</sub> O <sub>5</sub> )	10.00%
Soluble Potash (K <sub>2</sub> O)	10.00%
Sulfur (S)	1.0%
Boron (B)	0.03%
Cobalt (Co)	0.1%
Copper (Cu)	0.4%
Iron (Fe)	1.0%
Zinc (Zn)	0.4%

---

Derived from: Urea, Monoammonium Phosphate, Potassium Nitrate, Monopotassium Phosphate, Phosphoric Acid, Potassium Hydroxide, Iron Sulfate, Copper Sulfate, Zinc Sulfate, Cobalt Sulfate, and Sodium Borate.

*Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>*

### **Condition of Sale**

1. Seller warrants that this product consists of the ingredients specified and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use. No one, other than an officer of Seller, is authorized to make warranty, guarantee or direction concerning this product.
2. Because the time, place, rate of application and other conditions of use are beyond Seller's control, Seller's liability from handling, storage and use of this product is limited to replacement of product or refund of purchase price.

### **Storage Precautions**

Store in manufacturer's containers when possible. If not, store in polyolefin or polyethylene storage tanks. Do not store for extended periods in mild steel and only in approved fiberglass. Although stainless steel tanks are less prone to corrosion than mild steel, they are not recommended for extended storage. Do not use nylon fittings and valves. PVC or polypropylene valves and fittings are recommended.

CAUTION: KEEP OUT OF REACH OF CHILDREN

### **WARNING**

Harmful if swallowed. Avoid breathing spray mist. May cause irritation of nose, throat, and/or skin. Avoid contact with the eyes, skin and clothing. If swallowed: induce vomiting by sticking finger down throat. Never give anything by mouth to unconscious person. Get medical attention immediately. If in eyes, wash eyes with plenty of clear water for at least 15 minutes. Get medical attention immediately.

Keep stored above 32°F or 0°C  
DO NOT ALLOW TO FREEZE

Guaranteed by:  
EarthWorks  
1500 Uhler Road  
Easton, PA 18040  
800 732-TURF  
[www.earthworksfirst.com](http://www.earthworksfirst.com)

**F1399**